


POST SHORE - B Series HEAVY DUTY - EXPOSED THREAD

PUNTALES DE METAL AJUSTABLES - Serie B SERVICIO PESADO - ROSCA EXPUESTA

Adjustment with pin and levered handle



Heavy duty model Post Shore with exposed thread, cast collar with single lever type handle, end plates 4.75" x 4.75" x .32" (140mm x 140mm x 8mm), painted green.

Optional: Reinforced base, pin on cable.

Modelo de puntal de servicio pesado con roscas expuestas, cuello colado con una sola agarradera tipo palanca, placas extremo 140mm x 140mm x 8mm (4.75" x 4.75" x .32"), pintado de verde.

Opcional: Base reforzada, sujetador en cable.

ABLE

EXPORT, LLC
7475 NW 63rd Street
Miami, FL 33166-3603
Miami: (305) 593-2253
Fax: (305) 592-2793
USA WATS: 1-800-831-4564

AMERICAN SYSTEM
SISTEMA E.U.A.

METRIC SYSTEM
SISTEMA MÉTRICO



| | Length/Longitud: | External tube/Tubo externo: | Internal tube/Tubo interno: | Weight/Peso: |
|--|------------------|-----------------------------|-----------------------------|------------------|
| PS-1B 1,000/20' CONT. Special Order | 5'9" to/a 10'3" | 2.36" x .146" x 5'5" | 1.89" x .150" x 5'7" | 38 lbs./libras |
| PS-2B 800/20' CONT. | 6'6" to/a 11'0" | 2.36" x .146" x 5'5" | 1.89" x .150" x 6'5" | 41.7 lbs./libras |
| PS-3B 800/20' CONT. | 8'6" to/a 13'0" | 2.36" x .146" x 6'8" | 1.89" x .150" x 7'2" | 45.6 lbs./libras |
| PS-4B 450/20' CONT. | 10'6" to/a 16'0" | 2.36" x .146" x 6'7" | 1.89" x .150" x 10'5" | 56.1 lbs./libras |

ALLOWABLE LOADS IN LBS:

CARGAS PERMISIBLES EN KGS:

SAFETY FACTOR = 3:1 FACTOR DE SEGURIDAD = 3:1

| HEIGHT / ALTURA | 5' | 6' | 7' | 8' | 9' | 10' | 11' | 12' | 13' | 14' | 15' |
|-----------------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| | 1.52m | 1.83m | 2.13m | 2.44m | 2.74m | 3.05m | 3.35m | 3.66m | 3.96m | 4.27m | 4.57m |
| PS-1B | 10,600 4,808 | 9,800 4,445 | 8,800 3,992 | 7,800 3,538 | 6,800 3,084 | | | | | | |
| PS-2B | | | 7,300 3,311 | 7,150 3,243 | 7,000 3,175 | 5,600 2,540 | 4,200 1,905 | | | | |
| PS-3B | | | | | 6,500 2,948 | 6,200 2,812 | 5,950 2,698 | 4,600 2,086 | 3,350 1,519 | | |
| PS-4B | | | | | | 7,000 3,175 | 6,450 2,925 | 5,900 2,676 | 4,500 2,041 | 3,600 1,632 | 2,500 1,133 |